

# teknion boulevard

## Grade 1 Fabrics

|           |    |
|-----------|----|
| Anchorage | 2  |
| Aurora    | 4  |
| Chance    | 5  |
| Linea     | 6  |
| Lisbon    | 7  |
| Loopy     | 8  |
| Melody    | 9  |
| Merge     | 10 |
| Pinpoint  | 11 |
| Streak    | 12 |
| Tek       | 13 |
| Terrace   | 14 |


## Grade 2 Fabrics

|           |    |
|-----------|----|
| Cyclone   | 15 |
| Dashing   | 16 |
| Quadrille | 17 |


Click each fabric name in this contents page for more information.

# teknion boulevard

## Anchorage | Grade 1




Birch  
AN40




Green Apple  
AN41




Lapis  
AN42



Straw  
AN43




Wolf  
AN44




Goose  
AN45




Angora  
AN46




Cumin  
AN47




Asteroid  
AN48




Geranium  
AN49




Thistle  
AN50




Graphite  
AN51




Slate  
AN52



Quarry Blue  
AN53



Onyx  
AN54




Pumpkin  
AN55


| Content                                                                    | Width                      | Cleaning Code    | Weight       | Flammability Test & Result                                                |
|----------------------------------------------------------------------------|----------------------------|------------------|--------------|---------------------------------------------------------------------------|
| 35% Post-Consumer Recycled Polyester / 65% Pre-Consumer Recycled Polyester | 66 in min. usable / 168 cm | Water & Solvents | 15.0 oz / LY | ASTM E-84 - Passes California Technical Bulletin 117 / Section E - Passes |

# teknion boulevard


## Anchorage | Grade 1




Red Delicious  
AN56




Sunshine  
AN57



Vanilla  
AN61




Cobalt  
AN62




Cloud  
AN64


| Content                                                                    | Width                      | Cleaning Code    | Weight       | Flammability Test & Result                                                |
|----------------------------------------------------------------------------|----------------------------|------------------|--------------|---------------------------------------------------------------------------|
| 35% Post-Consumer Recycled Polyester / 65% Pre-Consumer Recycled Polyester | 66 in min. usable / 168 cm | Water & Solvents | 15.0 oz / LY | ASTM E-84 - Passes California Technical Bulletin 117 / Section E - Passes |




Cloud  
AU20




Seal  
AU21



Fog  
AU22



Pewter  
AU23




Granite  
AU24




Oat  
AU25




Coconut  
AU26



Latte  
AU27




Lake  
AU28




Frost  
AU29

| Content                                                       | Width          | Cleaning Code    | Weight        | Colorfastness to Light Test & Result | Flammability Test & Result | Crocking Test & Result                             | Breaking Strength Test & Result            |
|---------------------------------------------------------------|----------------|------------------|---------------|--------------------------------------|----------------------------|----------------------------------------------------|--------------------------------------------|
| 100% Polyester / 80% minimum Post-Consumer Recycled Polyester | 66 in / 168 cm | Water & Solvents | 12.94 oz / LY | AATCC-16A - Class 4.5                | CAL TB117-2013 - Passes    | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4 | ASTM D5034 - Warp: 307 lbs / Fill: 210 lbs |







Mist  
CN51




Dill  
CN52




Island  
CN53



Plaza  
CN54



Tranquil  
CN55



Navajo  
CN57



Prairie  
CN58



Cinder  
CN59




Oasis  
CN66


| Content                                                     | Width          | Cleaning Code    | Weight       | Colorfastness to Light Test & Result | Flammability Test & Result | Crocking Test & Result                             | Breaking Strength Test & Result             | Seam Slippage                           |
|-------------------------------------------------------------|----------------|------------------|--------------|--------------------------------------|----------------------------|----------------------------------------------------|---------------------------------------------|-----------------------------------------|
| 63% Virgin Polyester / 37% Post-Consumer Recycled Polyester | 66 in / 168 cm | Water & Solvents | 10.8 oz / LY | AATCC-16A - Class 4.5                | CAL TB117-2013 - Passes    | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5 | ASTM D5034-95 - Warp: 275 lb / Fill: 200 lb | ASTM D4034 - Warp: 104 lb / Fill: 77 lb |




Queue  
LN41




Cord  
LN42




Twine  
LN43




Thread  
LN44




Contour  
LN45



Silhouette  
LN46



Cable  
LN47



Route  
LN48

| Content                               | Width          | Cleaning Code    | Weight     | Colorfastness to Light Test & Result | Flammability Test & Result | Crocking Test & Result                             | Breaking Strength Test & Result             | Seam Slippage                           |
|---------------------------------------|----------------|------------------|------------|--------------------------------------|----------------------------|----------------------------------------------------|---------------------------------------------|-----------------------------------------|
| 100% Post-Consumer Recycled Polyester | 67 in / 168 cm | Water & Solvents | 11 oz / LY | AATCC-16A - Class 5                  | ASTM E84 - Class 1 or A    | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5 | ASTM D5034-95 - Warp: 100 lb / Fill: 100 lb | ASTM D4034 - Warp: 104 lb / Fill: 77 lb |

# teknion boulevard

## Lisbon | Grade 1



Moss  
LS17




Gesso  
LS11



Ivory  
LS14



Buff  
LS19




Henna  
LS15



Spa  
LS20



Navy  
LS18



Grey  
LS13



Dusk  
LS12



Nocturnal  
LS16

| Content                                              | Width        | Cleaning Code    | Weight     | Colorfastness to Light Test & Result | Flammability Test & Result | Crocking Test & Result                             | Breaking Strength Test & Result           | Seam Slippage                            |
|------------------------------------------------------|--------------|------------------|------------|--------------------------------------|----------------------------|----------------------------------------------------|-------------------------------------------|------------------------------------------|
| 67% Post-Consumer Recycled Polyester / 33% Polyester | 168 cm / 66" | Water & Solvents | 11 oz / LY | AATCC-16A - Class 4.5                | ASTM E-84 - Class 1 or A   | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4 | ASTM D5034<br>Warp: 293 lb / Fill: 240 lb | ASTM D4034 - Warp: 109 lb / Fill: 106 lb |



# teknion boulevard

## Loopy | Grade 1




Oyster  
LP60




Putty  
LP61



Marble  
LP62



Hazelnut  
LP63




Latte  
LP64



Bay  
LP65



Wild Rice  
LP66



Harbor  
LP67

| Content                        | Width | Cleaning Code    | Weight                  | Flammability<br>Test & Result                            | Crocking<br>Test & Result                            | Breaking Strength<br>Test & Result                |
|--------------------------------|-------|------------------|-------------------------|----------------------------------------------------------|------------------------------------------------------|---------------------------------------------------|
| 100% Post-Industrial Polyester | 66 in | Water & Solvents | 10.4 +/-<br>0.3 oz / LY | California Technical Bulletin<br>117 /Section E - Passes | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 3.5 | ASTM D5034-95 -<br>Warp: 266 lb /<br>Fill: 203 lb |



Melody | Grade 1



Spray  
ME40



Pond  
ME41



Sand Bar  
ME42




Silt  
ME43



Pebble  
ME44



Lake  
ME45



Gravel  
ME46



Boulder  
ME47

| Content                 | Width          | Cleaning Code    | Weight               | Colorfastness to Light Test & Result | Flammability Test & Result                            | Crocking Test & Result                               | Breaking Strength Test & Result             |
|-------------------------|----------------|------------------|----------------------|--------------------------------------|-------------------------------------------------------|------------------------------------------------------|---------------------------------------------|
| 100% Recycled Polyester | 66 in / 168 cm | Water & Solvents | 11.6 +/- 0.5 oz / LY | AATCC-16A - Class 4                  | California Technical Bulletin 117 /Section E - Passes | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 3.5 | ASTM D5034-95 - Warp: 225 lb / Fill: 100 lb |

# teknion boulevard

Merge | Grade 1




Fawn  
MG20



Marshmallow  
MG21



Driftwood  
MG22




Dove  
MG23




Graphite  
MG24




Slate  
MG25




Eucalyptus  
MG26



Fire Engine  
MG27




Mediterranean  
MG28




Midnight  
MG29


| Content                                                       | Width          | Cleaning Code    | Weight       | Colorfastness to Light Test & Result | Flammability Test & Result                    | Crocking Test & Result                             | Breaking Strength Test & Result            |
|---------------------------------------------------------------|----------------|------------------|--------------|--------------------------------------|-----------------------------------------------|----------------------------------------------------|--------------------------------------------|
| 100% Polyester / 75% minimum Post-Consumer Recycled Polyester | 66 in / 168 cm | Water & Solvents | 16.2 oz / LY | AATCC-16A - Class 4.5                | CAL TB117-2013 - Passes / ASTM E-84 - Class A | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4 | ASTM D5034 - Warp: 325 lbs / Fill: 275 lbs |




Bliss  
PN11




Delight  
PN12




Dune  
PN13




Infusion  
PN14




Ebony  
PN15




Fresh  
PN16




Carrot  
PN17



Splash  
PN18



Vibe  
PN19




Gala  
PN20

| Content                               | Width          | Cleaning Code    | Weight     | Colorfastness to Light Test & Result | Flammability Test & Result | Crocking Test & Result                             | Breaking Strength Test & Result             | Seam Slippage                           |
|---------------------------------------|----------------|------------------|------------|--------------------------------------|----------------------------|----------------------------------------------------|---------------------------------------------|-----------------------------------------|
| 100% Post-Consumer Recycled Polyester | 67 in / 168 cm | Water & Solvents | 11 oz / LY | AATCC-16A - Class 5                  | ASTM E84 - Class A         | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5 | ASTM D5034-95 - Warp: 100 lb / Fill: 100 lb | ASTM D4034 - Warp: 104 lb / Fill: 77 lb |



# teknion boulevard


Streak | Grade 1




Beach  
SR81




Shade  
SR86




Stretch  
SR88




Sprint  
SR89



Roll  
SR91




Dart  
SR92




Zoom  
SR93



Splash  
SR94



Whiz  
SR95




Flash  
SR96

| Content                                  | Width | Cleaning Code    | Weight     | Flammability<br>Test & Result | Crocking<br>Test & Result                          | Breaking Strength<br>Test & Result                |
|------------------------------------------|-------|------------------|------------|-------------------------------|----------------------------------------------------|---------------------------------------------------|
| 100% Post-Consumer<br>Recycled Polyester | 66 in | Water & Solvents | 11 oz / LY | ASTM E84 - Class A / Class 1  | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5 | ASTM D5034-95 -<br>Warp: 100 lb /<br>Fill: 100 lb |

# teknion boulevard

Tek | Grade 1




Finesse  
TX60



Grain  
TX61




Essence  
TX62




Warp  
TX64




Mesh  
TX67




Form  
TX69



Spice  
TX71




Glacier  
TX72




Spring  
TX73



Harmony  
TX74



Smoke  
TX75



Pebble  
TX76


| Content                                  | Width | Cleaning Code    | Weight     | Flammability<br>Test & Result | Crocking<br>Test & Result                          | Breaking Strength<br>Test & Result                |
|------------------------------------------|-------|------------------|------------|-------------------------------|----------------------------------------------------|---------------------------------------------------|
| 100% Post-Consumer<br>Recycled Polyester | 67 in | Water & Solvents | 11 oz / LY | ASTM E84 - Class A / Class 1  | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5 | ASTM D5034-95 -<br>Warp: 100 lb /<br>Fill: 100 lb |




## Terrace | Grade 1



Lotus  
TC60




Tigerlily  
TC61




Shadow  
TC62




Cobble  
TC63



Cherry Blossom  
TC64



Bluebell  
TC65



Apple  
TC66




Haze  
TC67




Cerise  
TC68




Twilight  
TC69




Wintergreen  
TC70




Ironwork  
TC71




Pine Cone  
TC72



Flirt  
TC73




Echo  
TC74




Glacier  
TC75

| Content                                                           | Width | Cleaning Code    | Weight        | Flammability<br>Test & Result | Crocking<br>Test & Result                          | Breaking Strength<br>Test & Result                | Seam Slippage                                     |
|-------------------------------------------------------------------|-------|------------------|---------------|-------------------------------|----------------------------------------------------|---------------------------------------------------|---------------------------------------------------|
| 70% Virgin Polyester /<br>30% Post-Consumer<br>Recycled Polyester | 48 in | Water & Solvents | 10.54 oz / LY | CAL TB117-<br>2013 - Passes   | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 3 | ASTM D5034-95 -<br>Warp: 279 lb /<br>Fill: 211 lb | ASTM D4034 -<br>Warp: 140.6 lb /<br>Fill: 68.6 lb |







Wrought Iron  
IM36




Stove Pipe  
IM37




Stainless  
IM40




Polished Pewter  
IM41




Welded Steel  
IM43




Etched Bronze  
IM44




Fired Titanium  
IM46




Chrome  
IM49



Dark Annealed  
IM50




Karat  
IM54




Red Metal  
IM55




Oxidized Bronze  
IM56



Bright Ray  
IM57



Bismuth Crystal  
IM58



Gallium Blue  
IM59

| Content        | Width          | Cleaning Code    | Weight       | Colorfastness to Light Test & Result | Flammability Test & Result                                                   | Crocking Test & Result                             | Breaking Strength Test & Result                   |
|----------------|----------------|------------------|--------------|--------------------------------------|------------------------------------------------------------------------------|----------------------------------------------------|---------------------------------------------------|
| 100% Polyester | 66 in / 168 cm | Water & Solvents | 15.5 oz / LY | AATCC-16A - Class 5                  | ASTM E-84 - Passes<br>California Technical Bulletin 117 / Section E - Passes | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4 | ASTM D5034-95 -<br>Warp: 190 lb /<br>Fill: 150 lb |


## Dashing | Grade 2



Classic Silver  
DS21



Refined Marble  
DS22




Antique Sage  
DS23



Polished Slate  
DS24



Genteel Beige  
DS25




Bespoke Tan  
DS26




Dapper Grey  
DS27

| Content                           | Width | Cleaning Code    | Weight       | Flammability<br>Test & Result | Crocking<br>Test & Result                          | Breaking Strength<br>Test & Result                    |
|-----------------------------------|-------|------------------|--------------|-------------------------------|----------------------------------------------------|-------------------------------------------------------|
| 100% Eco Intelligent<br>Polyester | 66 in | Water & Solvents | 10.9 oz / LY | CAL TB117-2013 - Class 5      | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5 | ASTM D5034-95 -<br>Warp: 240.6 lb /<br>Fill: 191.3 lb |


## Quadrille | Grade 2



Escapade  
QU30



Shenanigan  
QU31




Revelry  
QU32




Spring  
QU33




Regalia  
QU34



Soiree  
QU35




Zest  
QU36




Gambol  
QU37




Leisure  
QU38



Fair  
QU39



Fiesta  
QU40




Carnival  
QU41


| Content                                       | Width | Cleaning Code    | Weight        | Flammability<br>Test & Result | Crocking<br>Test & Result                          | Breaking Strength<br>Test & Result                    | Seam Slippage                                             |
|-----------------------------------------------|-------|------------------|---------------|-------------------------------|----------------------------------------------------|-------------------------------------------------------|-----------------------------------------------------------|
| 52.5% Polyester /<br>47.5% Recycled Polyester | 48 in | Water & Solvents | 12.11 oz / LY | CAL TB117-<br>2013 - Passes   | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4 | ASTM D5034-95 -<br>Warp: 249.5 lb /<br>Fill: 271.5 lb | ASTM 3597 D434-95 -<br>Warp: 73.02 lb /<br>Fill: 91.35 lb |




Quadrille | Grade 2




Spree  
QU42




Opus  
QU43



Jubilee  
QU44



Masquerade  
QU45



Cabaret  
QU46

| Content                                       | Width | Cleaning Code    | Weight        | Flammability<br>Test & Result | Crocking<br>Test & Result                          | Breaking Strength<br>Test & Result                    | Seam Slippage                                             |
|-----------------------------------------------|-------|------------------|---------------|-------------------------------|----------------------------------------------------|-------------------------------------------------------|-----------------------------------------------------------|
| 52.5% Polyester /<br>47.5% Recycled Polyester | 48 in | Water & Solvents | 12.11 oz / LY | CAL TB117-<br>2013 - Passes   | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4 | ASTM D5034-95 -<br>Warp: 249.5 lb /<br>Fill: 271.5 lb | ASTM 3597 D434-95 -<br>Warp: 73.02 lb /<br>Fill: 91.35 lb |

# teknion boulevard

| COLORWAY  | Content                                                                       | Width                         | Cleaning Code    | Weight                  | Abrasion | Colorfastness to Light<br>Test & Result | Flammability<br>Test & Result                                                   | Croaking<br>Test & Result                            | Breaking Strength<br>Test & Result                    | Seam Slippage                                                |
|-----------|-------------------------------------------------------------------------------|-------------------------------|------------------|-------------------------|----------|-----------------------------------------|---------------------------------------------------------------------------------|------------------------------------------------------|-------------------------------------------------------|--------------------------------------------------------------|
| ANCHORAGE | 35% Post-Consumer Recycled Polyester<br>/ 65% Pre-Consumer Recycled Polyester | 66 in min.<br>usable / 168 cm | Water & Solvents | 15.0 oz / LY            |          |                                         | ASTM E-84 - Passes<br>California Technical Bulletin 117<br>/Section E - Passes  |                                                      |                                                       |                                                              |
| AURORA    | 100% Polyester / 80% minimum<br>Post-Consumer Recycled Polyester              | 66 in / 168 cm                | Water & Solvents | 12.94 oz<br>/ LY        |          | AATCC-16A - Class 4.5                   | CAL TB117-2013 - Passes                                                         | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4   | ASTM D5034 -<br>Warp: 307 lbs /<br>Fill: 210 lbs      |                                                              |
| CHANCE    | 63% Virgin Polyester /<br>37% Post-Consumer Recycled Polyester                | 66 in / 168 cm                | Water & Solvents | 10.8 oz / LY            |          | AATCC-16A - Class 4.5                   | CAL TB117-2013 - Passes                                                         | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5   | ASTM D5034-95 -<br>Warp: 275 lb /<br>Fill: 200 lb     | ASTM D4034 -<br>Warp: 104 lb /<br>Fill: 77 lb                |
| LINEA     | 100% Post-Consumer Recycled<br>Polyester                                      | 67 in / 168 cm                | Water & Solvents | 11 oz / LY              |          | AATCC-16A - Class 5                     | ASTM E84 - Class 1 or A                                                         | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5   | ASTM D5034-95 -<br>Warp: 100 lb /<br>Fill: 100 lb     | ASTM D4034 -<br>Warp: 104 lb /<br>Fill: 77 lb                |
| LISBON    | 67% Post-Consumer Recycled Polyester<br>/ 33% Polyester                       | 168 cm / 66"                  | Water & Solvents | 9.09 oz / LY            |          | AATCC-16A - Class 4.5                   | ASTM E-84 - Class 1 or A                                                        | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4   | ASTM D5034<br>Warp: 293 lbs /<br>Fill: 240 lbs        | ASTM D4034<br>Warp: 109 lbs /<br>Fill: 106 lbs               |
| LOOPY     | 100% Post-Industrial Polyester                                                | 66 in                         | Water & Solvents | 10.4 +/-<br>0.3 oz / LY |          |                                         | California Technical Bulletin 117<br>/Section E - Passes                        | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 3.5 | ASTM D5034-95 -<br>Warp: 266 lb /<br>Fill: 203 lb     |                                                              |
| MELODY    | 100% Recycled Polyester                                                       | 66 in / 168 cm                | Water & Solvents | 11.6 +/-<br>0.5 oz / LY |          | AATCC-16A - Class 4                     | California Technical Bulletin 117<br>/Section E - Passes                        | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 3.5 | ASTM D5034-95 -<br>Warp: 225 lb /<br>Fill: 100 lb     |                                                              |
| MERGE     | 100% Polyester / 75% minimum<br>Post-Consumer Recycled Polyester              | 66 in / 168 cm                | Water & Solvents | 16.2 oz / LY            |          | AATCC-16A - Class 4.5                   | CAL TB117-2013 - Passes /<br>ASTM E-84 - Class A                                | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4   | ASTM D5034 -<br>Warp: 325 lbs /<br>Fill: 275 lbs      |                                                              |
| PINPOINT  | 100% Post-Consumer Recycled<br>Polyester                                      | 67 in / 168 cm                | Water & Solvents | 11 oz / LY              |          | AATCC-16A - Class 5                     | ASTM E84 - Class A                                                              | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5   | ASTM D5034-95 -<br>Warp: 100 lb /<br>Fill: 100 lb     | ASTM D4034 -<br>Warp: 104 lb /<br>Fill: 77 lb                |
| STREAK    | 100% Post-Consumer Recycled<br>Polyester                                      | 66 in                         | Water & Solvents | 11 oz / LY              |          |                                         | ASTM E84 - Class A / Class 1                                                    | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5   | ASTM D5034-95 -<br>Warp: 100 lb /<br>Fill: 100 lb     |                                                              |
| TEK       | 100% Post-Consumer Recycled<br>Polyester                                      | 67 in                         | Water & Solvents | 11 oz / LY              |          |                                         | ASTM E84 - Class A / Class 1                                                    | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5   | ASTM D5034-95 -<br>Warp: 100 lb /<br>Fill: 100 lb     |                                                              |
| TERRACE   | 70% Virgin Polyester /<br>30% Post-Consumer Recycled Polyester                | 48 in                         | Water & Solvents | 10.54 oz<br>/ LY        |          |                                         | CAL TB117-2013 - Passes                                                         | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 3   | ASTM D5034-95 -<br>Warp: 279 lb /<br>Fill: 211 lb     | ASTM D4034 -<br>Warp: 140.6 lb /<br>Fill: 68.6 lb            |
| CYCLONE   | 100% Polyester                                                                | 66 in / 168 cm                | Water & Solvents | 15.5 oz / LY            |          | AATCC-16A - Class 5                     | ASTM E-84 - Passes<br>California Technical Bulletin 117 /<br>Section E - Passes | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4   | ASTM D5034-95 -<br>Warp: 190 lb /<br>Fill: 150 lb     |                                                              |
| DASHING   | 100% Eco Intelligent Polyester                                                | 66 in                         | Water & Solvents | 10.9 oz / LY            |          |                                         | CAL TB117-2013 - Class 5                                                        | (Dry) AATCC-8 - Class 5<br>(Wet) AATCC-8 - Class 5   | ASTM D5034-95 -<br>Warp: 240.6 lb /<br>Fill: 191.3 lb |                                                              |
| QUADRILLE | 52.5% Polyester / 47.5% Recycled<br>Polyester                                 | 48 in                         | Water & Solvents | 12.11 oz<br>/ LY        |          |                                         | CAL TB117-2013 - Passes                                                         | (Dry) AATCC-8 - Class 4<br>(Wet) AATCC-8 - Class 4   | ASTM D5034-95 -<br>Warp: 249.5 lb /<br>Fill: 271.5 lb | ASTM 3597<br>D434-95 -<br>Warp: 73.02 lb /<br>Fill: 91.35 lb |