# LUUM

Welded

Name Welded

Designer Suzanne Tick

Style No. 4095

Collection Fabric of Space

Use Upholstery

#### Content

Coating: 100% Tekloom TPE Base Cloth: 100% Polyester Woven

### Abrasion

Wyzenbeek 105,000 double rubs

## Special

Characteristics Bleach Cleanable

#### Environmental

Chemical Finish Free DMF Free Heavy Metal Free Dyes **REACH** Regulation Complaint Complies with California Section 01350 VOC Emission Standards






Palladium 4095-05





Rose Torch 4095-07



Bond 4095-03

Synergy 4095-10

Soda Ash 4095-04



Charcoal Flux 4095-02




Synthesis 4095-11



Alliance 4095-01



Mingle 4095-09



Specification

Finish

Performance

Flame Retardancy

Maintenance

Environmental

Origin

# Welded 4095

Suzanne Tick

Use: Upholstery Content: Coating: 100% Tekloom TPE Base Cloth: 100% Polyester Woven Weight: 19.5 oz per linear yard Width: 54" Pattern Repeat: None Directional: Yes

Inherently Ink and Stain Resistant

Abrasion: ASTM D4157 Wyzenbeek 105,000 double rubs Breaking Strength: ASTM D5034 Warp 567.9 lbf, 431.3 Fill lbf Seam Slippage: ASTM D4034 Warp 102 lbf, Fill 108.5 lbf Colorfastness to Light: AATCC 16, Grade 4-5 at 40 Hours Colorfastness to Crocking: AATCC 8, Wet Class 5, Dry Class 5 Pilling: ASTM D3511 (Brush Pill), Class 5

Cal TB 117-2013

WS, Clean with either a water-based or solvent-based cleaning agent. Bleach Cleanable: 9% (10:1 Ratio), wipe with water after solution. For a list of approved cleaning products, please visit the resources section on the Luum website at www.luumtextiles.com

Chemical Finish Free DMF Free Heavy Metal Free REACH Regulation Compliant

Korea



Canada 877.705.LUUM luumtextiles.ca

cdn/us/int/05-22

 $\ensuremath{\mathbb{C}}$  Luum  $^{\mbox{\tiny TM}}$  2022, all rights reserved.  $^{\ast},{}^{\mbox{\tiny TM}}$  Trademarks used under license by Luum  ${}^{\mbox{\tiny TM}},$  Welded  ${}^{\mbox{\tiny TM}}$ \*Certification Marks owned by the Association for Contract Textiles. Inc. Multiple factors affect fabric durability and appearance retention.







Complies with California Section 01350 VOC Emission Standards

Dye lots may vary slightly from samples shown. Samples shown off the bolt.

USA 877.705.LUUM luumtextiles.com

International 919.464.2922 luumtextiles.com

Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.