

# LUUM

Touch Tone

**Collection**

Organized Complexity

**Designer**

Suzanne Tick

**Producer**

4117

**Collection**

Organized Complexity

**Use**

Upholstery

**Content**

90% Polyurethane +

10% Silicone

100% Polyester Backing

**Abrasion**

Wyzenbeek

500,000 double rubs

**Environmental**

Chemical Finish Free

PVC Free

DMF Free

Phthalate Free


Complies with California

Section 01350 VOC

Emission Standards




Silvoculture  
4117-04




Lily  
4117-06




Lacebark  
4117-05




Chaff  
4117-14



Thresh  
4117-15




Field Stone  
4117-13




Reave  
4117-03




Sycamore  
4117-07




Pyracantha  
4117-10




Liriope  
4117-21




Ice Plant  
4117-16




Skyway  
4117-17




Range  
4117-08



Mulch  
4117-09




Vineyard  
4117-11



Greenway  
4117-18




Levee  
4117-22




Fallow  
4117-12




Hawthorn  
4117-02



Ash  
4117-01



Linden  
4117-19



Aquaculture  
4117-20

Name **Touch Tone**

Style No. **4117**

Designer Suzanne Tick

Specification  
 Use: Upholstery  
 Content: 90% Polyurethane + 10% Silicone  
 100% Polyester Backing  
 Weight: 21 oz per linear yard  
 Width: 54"  
 Pattern Repeat: None  
 Directional: No

Finish Inherently Ink and Stain Resistant

Performance  
 Abrasion: ASTM D4157 Wyzenbeek 500,000 double rubs  
 Breaking Strength: ASTM D751 Warp 99.5 lbf, Fill 114.4 lbf  
 Colorfastness to Light: AATCC 16, Grade 4 at 200 Hours  
 Colorfastness to Crocking: AATCC 8, Wet Class 5, Dry Class 5  
 Adhesion of Coating: ASTM D751 Coating Cannot Be Removed  
 Tear Strength: ASTM D2261 Warp 6.2 lbf, Fill 5.8 lbf  
 Seam Strength: ASTM D751 Warp 101.9 lbf, Fill 102 lbf  
 Flex Resistance: CFFA 10 No cracking, whitening, crazing, or separation of coating  
 Hydrolysis: ISO 1419, 15 weeks

Flame Retardancy Cal TB 117-2013, NFPA 260

Maintenance  
 WS, Clean with either a water-based or solvent-based cleaning agent.  
 Bleach Cleanable: 9% (10:1 Ratio), wipe with water after solution.

Environmental  
 Chemical Finish Free  
 PVC Free  
 DMF Free  
 Phthalate Free  
 Complies with California Section 01350 VOC Emission Standards

Origin China



**Canada**  
 877.705.LUUM  
 luumtextiles.ca

**USA**  
 877.705.LUUM  
 luumtextiles.com

**International**  
 919.464.2922  
 luumtextiles.com

cdn/us/int/09-23

© Luum™ 2023, all rights reserved.  
 \*,™ Trademarks used under license by Luum™, Touch Tone™  
 \*Certification Marks owned by the Association for Contract Textiles, Inc.  
 Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.  
 Multiple factors affect fabric durability and appearance retention.

U4-SC-305-4117